

Material Safety Data Sheet

LashBase
Wongalee, Newlands Lane Waterlooville Hampshire PO76TP UK
Tel: 07779238177

1. PRODUCT IDENTIFICATION

Product Name : Max2 coating sealant

2. COMPOSITION / INFORMATION ON INGREDIENTS.

PURE WATER	<70-75%
PTFE - Polytetra Fluoro Ethylene (CAS : 9002-84-0)	>20-25%
Isopropyl Alcohol (CAS 67-63-0)	<5%

3. Hazard Identification

Physical Form : liquid

Major Health Hazards : Respiratory tract irritation, skin irritation, eye irritation.

Physical Hazards : Vapor may cause flash fire.

Potential Health Effects :

Inhalation - may cause irritation, nausea, vomiting, stomach pain, headache, drowsiness, symptoms of drunkenness, visual disturbances.

Skin Contact - may cause tingling sensation

Eye Contact - may cause irritation

Ingestion - may cause gastrointestinal irritation, nausea, diarrhea, symptoms of drunkenness,

and may cause kidney damage, liver damage in case of long term exposure.

Carcinogen Status :

OSHA - N NTP - N IARC - N

4. First Aid Measures

Inhalation : Remove from exposure immediately. Use a bag valve mask or similar device to perform artificial respiration (rescue breathing) if needed. Get medical aid.

Skin Contact : Remove contaminated clothing, jewelry, and shoes immediately. Wash with soap or mild detergent and large amounts of water until no evidence of chemical remains (at least 15-20 minutes). Get medical aid if needed.

Eye Contact : Wash eyes immediately with enough amount of water or normal saline, occasionally lifting upper and lower lids until no evidence of chemical remains.

Get medical aid if needed.

Ingestion : Never make an unconscious person vomit or drink fluids. When vomiting occurs, keep head lower than hips to help prevent aspiration. If person is unconscious, turn

head to side. Get medical attention immediately.

Note to Physician : For ingestion, consider gastric lavage and activated charcoal slurry.

5. Fire Fighting Measures

Fire and Explosion Hazards : The vapor is heavier than air.

page 2 of 4

Extinguishing Media : Alcohol resistant foam, carbon dioxide, water, regular dry chemical.

Large fires : Use alcohol-resistant foam or flood with water spray.

Fire Fighting : Move container away from fire area if it can be done without risk.

6. Accidental Release Measures

Occupational Release :

Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk. Reduce vapors with water spray.

Small spills : Absorb with sand or other non-combustible material.

Collect spilled material in appropriate container for disposal.

Large spills : Dike for later disposal.

Remove sources of ignition. Keep unnecessary people away, isolate hazard area and deny entry.

7. Handling and Storage

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Store in a tightly closed container, and in a cool, dry place. Ventilation required.

8. Exposure Controls, Personal Protection

Ventilation : Provide local exhaust ventilation system.

Eye Protection : Wear splash resistant safety goggles.

Clothing : Wear appropriate chemical resistant clothing.

Gloves : Wear appropriate chemical resistant gloves.

Respirator : Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

9. Physical Property Information

Form : Slightly Ivory Emulsion

Odor : Slightly perfume

Boiling Point : 180°F

Specific Gravity : Approx. 1.0

Solubility in water : Appreciable

Ph : Approx. 2.5

10. Stability and Reactivity

Reactivity : Stable at normal temperatures and pressure.

Condition to Avoid : Avoid heat, flames, sparks and other sources of ignition.

Containers may rupture or explode if exposed to heat.

Incompatibility(Material to avoid) : Acids, armines, halogens, halo carbons, oxidizing material, salts, peroxides, combustible materials.

OSHA PROCESS SAFETY (29CFR1910.119) : N

STATE REGULATIONS :

California Proposition 65 : N

EUROPEAN REGULATIONS :

EC RISK AND SAFETY PHRASES :

S 2 Keep out of reach of children.

S 9 Keep container in a well-ventilated place.

S 16 Keep away from sources of ignition - No smoking.

S 23 Do not breathe gas, fumes, vapour, or spray.

S 33 Take precautionary measures against static discharges.